

Conwed Fibers * Hydro Mulch * 1000 Wood Fiber

Now with TriFlo! — makes the best hydraulic mulch even better!

- Improves moisture retention
- Improves the suspension of mulch, seed and fertilizer within the slurry and prevents the dewatering of the fiber mulch
- Improves the application of hydraulic mulch in a more uniform layer for better coverage and enhanced product performance
- Improves application efficiency by increasing shooting distance and enhancing hose performance—greatly reducing downtime associated with clogging



Thermally Refined[®] manufacturing process provides a higher quality wood mulch and unsurpassed performance.

- Hydro Mulch * 1000 provides maximum soil coverage due to its 100% Thermally Refined * wood fiber
- Utilizes heat and pressure that breaks wood down into more fibrous material with greater surface area that results in better yield and coverage
- Delivers up to 50% more water-holding capacity than atmospherically refined wood mulches
- Creates an interlocking matrix for better erosion control protection and allows for improved oxygen transfer
- Creates a near perfect environment for faster germination



Product Composition:	Slope Gradient/Condition	Rate
Thermally Refined [®] Wood Fibers – 87% ± 3%	≤ 4H:1V	2000 lb/acre
Proprietary Emulsifying Agents (TriFlo) – 1% ± 0.5%	> 4H:1V and ≤ 3H:1V	2500 lb/acre
Moisture Content – 12% ± 3%	> 3H:1V and ≤ 2H:1V	3000 lb/acre
(40) 50-lb bales per pallet		



PROFILE Products LLC
750 Lake Cook Road • Suite 440 • Buffalo Grove, IL 60089

Distributed By:
granite
SEED
and erosion control

1697 West 2100 North
Lehi, Utah 84043
801.768.4422 | 801.561.1456
Fax 801.768.3967
info@graniteseed.com
www.graniteseed.com